

TECHNICAL SPECIFICATION**CR-1200****120 WATT SOLID STATE PUBLIC ADDRESS AMPLIFIER**Input Power Supply
a) AC Mains Operation
b) Battery OperationSingle Phase 240 V, 50 Hz +- 10%
12 V Car Battery3amps AC Fuse
10amps DC FuseOutput Power
a) Peak Music
b) Rated RMS120 watts
100 wattsInputs
a) Microphones
b) Aux-
Phone/Type5
1Sensitivity
0.6mv
70mvImpedance
3.3 K Ohms
300 K Ohms

Frequency Response

60Hz-16,000 Hz +-3dB

Total Harmonic Distortion

Less Than 2%

Signal/Noise Ratio

Better than 60dB

Controls
a) Input gain
b) Bass
c) Treble
d) MasterSeparate gain control for each of the 4 inputs
+- 12dB at 100Hz
+- 12dB at 10,000 Hz
Output Volume Control

Output Terminations

4,8 and 16 ohms

a) Impedance b) Voltage c) Record/Playback	70V and 100V DIN termination ("Line out'-1mv/1K ohms)
Dimensions (L x D x H)	410(L) x 275 (D) X 130 (H) mm chassy X 142-with bushes
Weight	10.5 Kg.