


Central Broadcast System Components



TK-A15E Emergency Panel

- Used to produce Alarm Sound
- Alarm triggered siren or pre-recorded output
- 1 minute digital record/play IC

TK-A16T Programmable Timer

- Controls 6 external units for daily/weekly programs
- Graphic L C D display with rotary dial
- Set Alarm input and output

TK-A18I Telephone Interface

- Automatically answers incoming calls
- Phone call can be broadcast over PA system

TK-A19A Alarm Matrix

- Intelligent fire warning connection
- 30 zones, automatic activation. Expandable To 128 by adding modules
- 2 additional zones on either side of the effected zone, also on auto-trigger.
- Programmable

TK-A20S Switching Power

- 10 channels Alarm input
- Alarm signal activates 24VDC outputs
- Forced outputs (24 v) overrides over signal inputs

TK -A21M Amp Auto Change over Switch

- Monitors upto 4 amplifiers automatically
- 4 independent channels, 4 main /4 sub amps
- Automatically change over from main to sub amp
- Manual/automatic cut over function
- Status display of operating amplifiers

NOTE: The Company's policy is continuous improvement of its products.
We therefore reserve the right of any deviation from illustration or specification without notice.

25, Jawaharlal Nehru Road,

BANGALORE KOLKATA NEW DELHI FACTORY

9, Sri Narasimharaja Road P.O. Box No. 6673 Bangalore - 560 002

09341272583

Tel.: 080 2235640

P.Ó. Box No. 2589 Kolkata - 700 087 Tel.: 98 103 56563

65, Electronic City, Hosur Road., Bangalore - 561 158

 Tel.: 033 22493831
 Tel.: 080 285 20151

 Fax: 033 22496626
 : 080 28520556

"Gyan Ghar". 14th Road, Khar (W), Mumbai -400 052 Tel: 2604 7394, 2604 2648, 2605 1620. Fax : 2605 9454 E- Mail : motwane_g@vsnl.net / ctrcpl@yahoo.co.in (Website : www.chicago-radio.net)



PA Series System Components



TK-A25L Lightning Protector

- 5 inputs, 5 outputs
- Prevents lightning from entering the system
- Automatically grounds outputs when struck by lightning

TK-A28S Sequence Controller

- PA system power source management
- Turns on/off upto 16 amplifier units
- Automatic/manual control through timer
- Power aggregate capacity: 4.5KVA

TK-A30H Graphic Equalizer

- 30 frequency bands adjustment
- LED level and peak indicator
- Reset switch

TK-A48S Audio Matrix

- 4 sound source inputs to be routed over 8 amplifier
- Easy to select sources and outputs
- Multi-source sound broadcasting
- Automatically sends alarm

TK-A816S Digital Audio Matrix

- Large graphical multi-menu LCD display
- Broadcasting, zone paging and emergency alarm simultaneously
- 8 line inputs; 16 amplifier outputs
- 16 line alarm matrix signal

TK-MP3 MP3 Player/Recorder

- Computer controlled, soft touch, LCD display
- 64M EMS memory
- Automatic or manual play, weekly/daily, 99 segments
- USB transmission

NOTE: The Company's policy is continuous improvement of its products.
We therefore reserve the right of any deviation from illustration or specification without notice.

BANGALORE KOLKATA NEW DELHI FACTORY

9, Sri Narasimharaja Road P.O. Box No. 6673 Bangalore - 560 002

Tel.: 080 2235640 09341272583 25, Jawaharlal Nehru Road, P.O. Box No. 2589 Kolkata - 700 087

Tel.: 033 22493831 Fax: 033 22496626 Tel.: 98 103 56563 65, Electronic City, Hosur Road., Bangalore - 561 158

> Tel.: 080 285 20151 : 080 28520556


"Gyan Ghar". 14th Road, Khar (W), Mumbai -400 052 Tel: 2604 7394, 2604 2648, 2605 1620. Fax : 2605 9454 E- Mail : motwane_g@vsnl.net / ctrcpl@yahoo.co.in (Website : www.chicago-radio.net)



MOTWANE PRIVATE LIMITED

Central Broadcast System Components





TK-A10R Paging Microphone

- Remote Controls TK-A 10P paging selector
- Distance up to 500 mtr
- Built-in chime generator
- Expandable, up to 3 additional units
- Mute function Mic output overides other inputs as per TK A 10P

TK-A10P Paging Selector

- 10 zone selector
- 10 alarm inputs / output activation
- Remote control connection to A 10 R
- 2 microphone, 2 line inputs
- Built-in chime generator
- Priority Input of Mic 1 / link 1 overides other signal inputs

TK-A11P Pre-Amplifier

- 5 Mic, 3 Aux, 2 Priority inputs
- Priority inputs overide other inputs
- Individual gain, bass, and treble controls
- 5-element LED level meter
- Mute function to mute other inputs when Mic 1 inputs in use

TK-A12M Monitor Panel

- Used mainly with A 13 D
- Monitors 10 channels 10 outputs channels of 10 different amps via selection switch
- Built-in internal speaker with volume control
- 5-element LED level indicator

TK-A13B Speaker Selector

- Switches 1 amplifier output to 10 zones zones through selector switches1-10
- 1 BGM amplifier, 1 emergency amplifier inputs
- Individual LED indicators

TK-A13D Speaker Selector

- 2 Amplifier inout
- Switches 1 amplifier outputs to 10 zones through selector switches1-10
- 1 BGM amplifier, 1 emergency amplifier inputs
- Individual LED indicators
- 10 alarm inputs / activation outputs

NOTE: The Company's policy is continuous improvement of its products.

We therefore reserve the right of any deviation from illustration or specification without notice.