

TECHNICAL SPECIFICATION			
CR-800	80 WATT SOLID STATE PUBLIC ADDRESS AMPLIFIER		
Input Power Supply a) AC Mains Operation b) Battery Operation	Single Phase 240 V, 50 Hz +- 10% 12 V Car Battery	2amps AC Fuse 10amps DC Fuse	
Output Power a) Peak Music b) Rated RMS	90 watts 80 watts		
Inputs a) Microphones b) Aux-Phone/Type	4 1	Sensitivity 0.6mv 70mv	Impedance 3.3 K Ohms 300 K Ohms
Frequency Response	50Hz-16,000 Hz +-2dB		
Total Harmonic Distortion	Less Than 2%		
Signal/Noise Ratio	Better than 60dB		
Controls a) Input gain b) Bass c) Treble d) Master	Separate gain control for each of the 4 inputs +- 11dB at 100Hz +- 12dB at 10,000 Hz Output Volume Control		
Output Terminations	4,8 and 16 ohms		

a) Impedance b) Voltage c) Record/Playback	100V DIN termination ("Line out'-1mv/1K ohms)
Dimensions (L x D x H)	360(L) x 275 (D) X 117 (H) mm chassy X 132-with bushes
Weight	10.5 Kg.